

MSDS Report

Applicant's name	SHENZHEN SUNHE ENERGY C	O., LTD.	
Applicant's Address	No.44, Hengtang Rd., Shijing Stre	eet, Pingshan District, S	henzhen China
Name of Sample	Li-ion Cell	<u>(1)</u>	(c ⁴)
Model	SH103035		
Nominal Voltage	3.7V		
Rated Capacity	1000mAh, 3.7Wh		
Weight	16.4g		
Size (L×W×T)	(33.5×29.5×9.8)mm		
Prepared By	Shenzhen TCT Testing Technolog 2101 & 2201, Zhenchang Factory Subdistrict, Bao'an District, Shenz	Renshan Industrial Zo	
Report No.	TCT221209M037		

Written by:	Mollie wu	Approved by:	lows w	
(.C)	(.C.)	(.G.)		(.G.)

Inspected by: Effective Date: 2023. 01. 01

Report No.: TCT221209M037

This report shall not be reproduced except in full, without the written approval of Shenzhen TCT Testing Technology Co



Section 1- Chemic	al Product & Com	npany Ider	ntification			
Name of Sample	Li-ion Cell					
Manufacturer's name	SHENZHEN SUNHE	ENERGY CO.	LTD.			
Manufacturer's Address	No.44, Hengtang Rd.,	Shijing Street	, Pingshan Di	istrict, Shenzh	nen China	
Contact Person	Mr. Tan					
Tel	+86-755-88893866					
Emergency Tel	+86-755-88893866	(C)				
E-mail	tanzhilong@sunhetecl	h.com				

Section 2- Hazards Identification			
Classification of Danger	See section 14.	(
Primary Route(s) of Exposure	Eye, skin contact, ingestion.		
Health Hazard	The batteries are not hazardous when used according to the instructions of manufacturer under normal conditions. In case of abuse, there's Hazard of rupture, fire, heat, leakage of internal components, which could cause casualty loss. Abuses including but not limited to the following cases: charged for long time, short circuited, put into fire, whacked with hard object, punctured with acute object, crushed, and broken.		

Report No.: TCT221209M037 Page 2 of 8 Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com



Section 3- Composition/Information on Ingredients				
Chemical Name	Concentration or concentration ranges (%)	CAS Number		
Lithium Cobalt Oxide (CoLiO ₂)	15-40	12190-79-3		
Graphite	10-30	7782-42-5		
Phosphate(1-), hexafluoro-, lithium	10-30	21324-40-3		
Copper	7-13	7440-50-8		
Aluminum foil	5-10	7429-90-5		
Nickel	1-5	7440-02-0		

Labeling according to EC directives.

No symbol and Hazard phrase are required.

Note: CAS number is Chemical Abstract Service Registry Number.

N/A=Not apply.

Section 4- First Aid Measures		
Eye	Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.	
Skin	Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes. Get medical aid.	
Inhalation	Remove from exposure and move to fresh air immediately. Use oxygen if available.	
Ingestion	Ingesting damaged batteries, do not induce vomiting or give food or drink. Seek medical attention immediately.	

Section 5- Fire Fi	ighting Measur	es		
Characteristics of Hazard	Dusts at sufficient of generates toxic fundament		n explosive mixtures with air.	Combustion
Hazardous Combustion Products	Carbon dioxide.	(C)	(C ¹)	



Fire-extinguishing Methods and Extinguishing Media	For small fires, use water spray, dry chemical, carbon dioxide or chemical foam.
Attention in Fire-extinguishing	Wear self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6- Accidental Release Measures			
Personal Precautions, protective equipment, and emergency procedures	In case of rupture. Attention! Corrosive material. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Refer to protective measures listed in Sections 7 and 8.		
Environmental Precautions	Prevent product from contaminating soil and from entering sewers or waterways.		
Methods and materials for Containment	Stop the leak if safe to do so. Contain the spilled liquid with dry sand or earth. Clean up spills immediately.		
Methods and materials for cleaning up	Absorb spilled material with an inert absorbent (dry sand or earth). Scoop contaminated absorbent into an acceptable waste container. Collect all contaminated absorbent and dispose of according to directions in Section 13. Scrub the area with detergent and water; collect all contaminated wash water for proper disposal.		

Section 7- Handling and Storage			
Handling	The battery may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.		
Storage	Store in a cool, dry, well-ventilated area away from incompatible substances. Store locked up. Keep out of the reach of children.		
Other Precautions	In case of rupture. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Use personal protection equipment.		



Section 8 - Exposure Controls/Personal Protection			
Engineering Controls	Use adequate ventilation to keep airborne concentrations low. If used under conditions that generate particulates, the ACGIH TLV-TWA of 3mg/m³ respirable fraction (10mg/m³ total) should be observed.		
	Eye and Face Protection: None required for consumer use. If there is a Hazard of contact: Tight sealing safety goggles. Face protection shield.		
Personal Protective Equipment	Skin and Body Protection: None required for consumer use. If there is a Hazard of contact: Wear protective gloves and protective clothing.		
	Respiratory Protection: No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.		

Section 9- Phy	sical and Chemical Properties	
	Appearance: Prismatic	
Physical State	Color: Silver	
(C°)	Odour: If leaking, smells of medical ether.	
Change in condit	tion	
рН	Not applicable as supplied.	
Flash Point	Not applicable unless individual components exposed.	0
Flammability	Not applicable unless individual components exposed.	
Relative density:	Not applicable unless individual components exposed.	
Solubility (water)	Not applicable unless individual components exposed.	
Solubility (other)	Not applicable unless individual components exposed.	

Section 10 – Stability and Reactivity	
Chemical Stability	Stable under recommended storage conditions.
Possibility of Hazardous Reactions	None under normal processing.
Conditions to Avoid	Exposure to air or moisture over prolonged periods.

Page 5 of 8 http://www.tct-lab.com Report No.: TCT221209M037 Hotline: 400-6611-140 Tel: 86-755-27673339

Fax: 86-755-27673332



Incompatible materials	Acids, Oxidizing agents, Bases.
Hazardous Decomposition Products	Carbon oxides.

Section 11 – Toxicological Information	on
Irritation	In the event of exposure to internal contents, vapour fumes may be very irritating to the eyes and skin.
Sensitization	Not Available.
Reproductive Toxicity	Not Available.
Toxicologically Synergistic Materials	Not Available.

Section 12-Ecological Information	
General note:	Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Anticipated behavior of a chemical product in environment/possible environmental impact/ ecotoxicity	Not Available.

Section 13 – Disposal Considerations	
Waste Treatment	Recycle or dispose of in accordance with government, state & local regulations.
Attention for Waste Treatment	Deserted batteries shouldn't be treated as ordinary trash. Shouldn't be thrown into fire or placed in high temperature. Shouldn't be dissected, pierced, crushed or treated similarly. Best disposal method is recycling.

Section 14 – Transport Ir	formation
UN number	3480 & 3481
Proper shipping name	Lithium ion batteries (limited to a maximum of 30% SoC) or; Lithium ion batteries packed with equipment (including lithium ion polymer batteries) or; Lithium ion batteries contained in equipments (including lithium ion
	polymer batteries).



r needs to comply with, in utside their premises ance with International Civil Aviation national Air Transport Association is (PI) 965 Section II.
national Air Transport Association is (PI) 965 Section IB, PI 966 Section II
e of IATA DGR 64 th (2023 Edition) for
o IMDG Code 2020 Edition (Amdt ision 188.
Department of Transportation (DOT) rials Regulations if shipped in 5.
the provisions of United Nations oe (UNECE) ADR/ADN if they meet the n 188 of Chapter 3.3. Applicable as from
3

Section 15 - Regulatory Information

Dangerous Goods Regulations

Recommendations on the Transport of Dangerous Goods-Model Regulations (22nd revised edition)

Recommendations on the Transport of Dangerous Goods-Manual of Tests and Criteria

International Air Transport Association (IATA)

International Maritime Dangerous Goods (IMDG Code 2020 Edition Amdt 40-20)

Technical Instructions for the Safe Transport of Dangerous Goods

tests set out in Subsection 38.3 of the UN Manual of Tests and Criteria.

Classification and code of dangerous goods (GB 6944-2012)

2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Toxic Substance Control Act (TSCA)

Code of Federal Regulations

In accordance with all Federal, State and local laws

Report No.: TCT221209M037 Page 7 of 8
Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com






Section 16 – Additional Information

MSDS creation date: 2023 Version: 1.0

Sample photo:





To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

The data/information contained herein has been reviewed and approved for general release on the basis that this document contains no export controlled information.

******End of report*****

Shenzhen TCT Testing Technology Co., Ltd.

2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen,

Guangdong, China

Report Search Number: TCT221209M037 Search System: http://www.tct-lab.com